

8360W

DC BATTERY BACKUP CAPABLE CHAIN DRIVE WI-FI® GARAGE DOOR OPENER

Customizable advanced security and reliability.



KEY FEATURES

CUSTOMIZABLE OPENER
to Meet Homeowners' Needs

WI-FI
Built In

AUTOMATIC GARAGE DOOR LOCK CAPABLE

BATTERY BACKUP CAPABLE

SECURE

AUTOMATIC GARAGE DOOR LOCK CAPABLE: DEADBOLT LOCKS THE GARAGE DOOR, MAKING IT VIRTUALLY IMPENETRABLE (2 MAX., SOLD SEPARATELY).

SECURITY+ 2.0® SAFEGUARDS GARAGE ACCESS BY SENDING A NEW CODE WITH EVERY CLICK.

POSILOCK® ELECTRONICALLY PROTECTS AGAINST FORCED OPENINGS.

ALERT-2-CLOSE SIGNALS WHEN A DOOR IS BEING CLOSED BY MyQ®.

MOTION DETECTOR LIGHTS THE WAY AUTOMATICALLY.

THE PROTECTOR SYSTEM® INVISIBLE LIGHT BEAM AUTO-REVERSES THE DOOR IF THERE IS AN OBSTRUCTION.

RELIABLE

BATTERY BACKUP CAPABLE: ENSURES GARAGE ACCESS DURING POWER OUTAGES (SOLD SEPARATELY).

SOFT START/STOP FOR SMOOTH OPERATION.

DC MOTOR IS PURPOSEFULLY DESIGNED AND BUILT TO LAST.

CHAIN DRIVE SYSTEM FOR STEADY PERFORMANCE AND INDUSTRIAL STRENGTH.

WARRANTY LIFETIME MOTOR, 1-YEAR PARTS AND ACCESSORIES.

SMART

BUILT-IN WI-FI FOR THE EASIEST WAY TO CONNECT THE GARAGE.

FREE MyQ MOBILE APP SO USERS KNOW THEIR HOME IS SECURE.

REAL-TIME ALERTS INDICATE THE STATUS OF THE GARAGE DOOR VIA EMAIL OR PUSH NOTIFICATIONS.

MONITOR AND CONTROL THE OPENER FROM ANYWHERE USING MOBILE DEVICES.

INCLUDED ACCESSORIES:

MOTION DETECTING CONTROL PANEL
Activates the opener's lights automatically.



886LMW

3-BUTTON REMOTE CONTROL
Operates up to 3 openers or MyQ Light Accessories.



893LM

POWERFUL ADD-ONS:

BATTERY BACKUP CAPABLE
Powers up the opener when the power's out.



485LM

AUTOMATIC GARAGE DOOR LOCK CAPABLE
Deadbolts the garage door automatically every time it closes.



841LM

REMOTE LIGHT CONTROL
Plug in any lamp to this device to control it with a smartphone or garage remote.



825LM

MINI UNIVERSAL REMOTE CONTROL
Compact and portable to provide quick, easy garage access.



374UT

WIRELESS KEYLESS ENTRY
Provides convenient, secure access from outside the garage with a 4-digit PIN.



877LM

PRODUCT GUIDE 8360W

DC BATTERY BACKUP CAPABLE CHAIN DRIVE WI-FI GARAGE DOOR OPENER

LiftMaster®

8360W

MASTERFUL ENGINEERING.

DC BATTERY BACKUP CAPABLE
CHAIN DRIVE WI-FI®
GARAGE DOOR OPENER

MOTOR

- 12V DC
- 53 RPM
- Automatic Thermal Protection

POWER

- 120V AC
- 60 Hz Voltage
- 2.7A Current Rating
- UL Listed
- 4' Power Cord (3-Prong)

MECHANICS

- **Steel Chassis, T-Rail and Trolley**
- **Full Reinforced Chain Drive Mechanism** (63:1 Gear Reduction and Adjustable Door Arm)
- **Auto-Force** Adjustment for Changing Weather and Environmental Conditions
- **Electronic Limits** for Easy Setup
- **DC Wi-Fi Logic Board** with Built-In Surge Suppressor (for Replacement Logic Boards, Order Part 050DCTWFLK)
- **2 Lock Terminals** Allow up to 2 Locks to Be Connected (Sold Separately)

7.5"



19"

10.5"

DIMENSIONS

Rail Options	7'	8'	10'
Installed Length	128"	140"	164"
Max. Opening	7'6"	8'6"	10'6"

Headroom Clearance Required: 2"

8"

Per second for door to move upward

SPEED

6.5"

Per second for door to move downward

STANDARD SPECS.

SECURITY

SECURITY+ 2.0®

RADIO CONTROLS

Operating Range: ~200'

Operating Temperature: -30°F to 150°F

3-Button Remote Control (893LM)

- Remote Control: 310, 315 and 390 MHz Tri-Band*
- Garage Door Opener: Frequency Agile on 310, 315 and 390 MHz
- Anti-Burglary Coding

*Tri-band on Security+ 2.0 coding only. Premium remote control is backwards compatible to all LiftMaster® openers manufactured since January 1993.

ENCRYPTED CONTROLS

Motion Detecting Control Panel (886LMW)

- Program Remote Controls
- Maintenance Alert System
- Easy Wi-Fi Setup

SMART

MyQ® RADIO

902-928 MHz
50-Channel FHSS
(Frequency Hopping Spread Spectrum)

- Provides 2-way communication from garage door opener and MyQ Accessories.
- Enables monitoring and control of garage door openers and lighting controls via smartphone, tablet or computer.

HOMELINK® COMPATIBLE (VERSION 4.0 OR HIGHER*)

*May require an external adapter depending on the model and year of your vehicle. Visit HomeLink.com for additional information.

ELECTRICAL

LIGHTING



- Max. 2 100-Watt Lightbulbs
- Adjustable Time
- Enhanced CFL (Compact Fluorescent) Compatible, Max. 26 Watts
- Disabled in Battery Backup Mode

SHIPPING.

SHIPPING WEIGHT

(in lbs.)

18
HEAD20
RAIL4
BATTERY
BACKUP
(OPTIONAL)3
AUTOMATIC
GARAGE
DOOR LOCK
(OPTIONAL)

CARTONS (4)

CARTON 1: 20" x 12" x 10"

- Garage Door Opener Head (8360W)
- Motion Detecting Control Panel (886LMW)
- 3-Button Remote Control (893LM)
- The Protector System® Safety Reversing Sensors

CARTON 2: 10'4" x 5" x 5"

- Assembled Solid-Steel Chain T-Rail

CARTON 3 (OPTIONAL): 5.31" x 4.63" x 5.13"

- Battery (485LM)

CARTON 4 (OPTIONAL): 8" x 4.5" x 4"

- Automatic Garage Door Lock (841LM)

SAFETY AND SECURITY.

- Automatic Garage Door Lock Capable (2 Max.)
- Alert-2-Close/Unattended Close Operation†
- Motion Detection Feature on Control Panel
- Emergency/Quick Release
- Automatic Trolley Reconnect
- Ventilation/Pet Opening
- Down Safety Reverse
- Safety Beam Obstruction Turns Lights On
- Maintenance Alert System
- Garage Door Opener Capacity of up to 24 Remote Controls, 2 Wireless Keyless Entry Systems and 16 MyQ Devices



© 2017 LiftMaster All Rights Reserved
300 Windsor Drive, Oak Brook, IL 60523
LiftMaster.com

Wi-Fi® is a registered trademark of Wi-Fi Alliance

UL and the UL logo are trademarks of UL LLC © 2017 All Rights Reserved.

HomeLink® and the HomeLink House® logo are registered trademarks of Gentex Corporation
LMGDENPG8360A 0617

† Note: to reduce the risk of injury to persons, only use Alert-2-Close/Unattended Close Operation features when installed with a sectional door.

LiftMaster®